

Certificate of Analysis

PRODUCT NAME : XTeer PSF (Power Steering Fluid)

LOT NO : 170210/21K

DATE : 2017. 02. 10

ITEM	METHOD	SPECIFICATION	RESULT	
APPEARANCE	Visual	Bright & Clear	Bright & Clear	
SPECIFIC GRAVITY (15/4°C)	KS M 2002	Report	0.8559	
VISCOSITY (40°C, mm ² /s)	KS M ISO 3104	28.8~35.2	30.18	
VISCOSITY (40°C, mm ² /s)	KS M ISO 3104	Report	5.315	
VISCOSITY INDEX	KS M ISO 3104	Min. 90	104	
POUR POINT, °C	KS M ISO 3016	Max. -24	-45	
FLASH POINT, °C	KS M ISO 2592	Min. 170	218	
RUST PREVENTING	KS M ISO 2009	No Rust	No Rust	
COPPER CORROSION(100°C, 3hr)	KS M ISO 2160	Max. 1	1a	
DEMULSIBILITY (54°C, min)	KS M ISO 6616	Min. 30	5	
WATER CONTENT, PPM	KS M ISO 10336	Min. 500	80	
Foam Test (ml/ml)	SEQ.1	KS M ISO 6247	Max. 65/0	10/0
	SEQ.2		Max. 65/0	30/0
	SEQ.3		Max. 65/0	10/0

Hyundai Oilbank certifies the above statement of quality to be true and correct.

Seong-ho Cho

Seong-ho Cho
Lubricants Production & Technology Team
Hyundai Oilbank Co., Ltd.