

Certificate of Analysis

PRODUCT NAME: XTeer Diesel Ultra C3 5W30			DATE : 2016.07.13
ITEM	METHOD	SPECIFICATION	RESULT
APPEARANCE(Conc.)	Visual	Report	Clear & Bright
DENSITY (15°C, kg/m ³)	KS M 2002	Report	854.1
VISCOSITY (40°C, mm ² /s)	KS M ISO 3104	Report	65.93
VISCOSITY (100°C, mm ² /s)	KS M ISO 3104	9.3 ~ 12.5	11.24
VISOSITY INDEX	KS M ISO 2909	Report	164
CCS (-30°C, mPas·s)	KS M 2121	Max. 6600	6127
FLASH POINT (°C, COC)	KS M ISO 2592	Min. 190	224
TBN (mg KOH/g)	ASTM D 2896	Report	8.0
Sulfur (mass %)	ASTM D 4951	Report	0.16
Sulfated ash (mass %)	ASTM D 874	Report	0.79
POUR POINT (°C)	KS M ISO 3016	Max. -30.0	-36

Hyundai Oilbank certifies the above statement of quality to be true and correct.

Seong-ho Cho
Team Leader of Lubricants Technology Team
Hyundai Oilbank Co., Ltd.

Hyundai Oilbank Co., Ltd.

20F Yonsei Bldg, 10 Tongil-ro, Jung-gu, Seoul, Korea

Tel : 82-2-2004-3381

Fax : 82-2-2004-3258

